

PVC GLUE K71RT/RW (Transparent/White)

1. Description

COMPOUNDING SOLUTIONS

The PVC Glue K71RT/RW is a transparent or white liquid solvent based PVC contact glue for the cold gluing of PVC to PVC. It dries extremely fast and is particularly interesting for narrow work. After the curing time, a strong bond is obtained. The Glue can be used for rigid or non-rigid PVC.

The colour of the K71RT/RW glue is unalterable and has a high thermal stability, which makes it particularly suitable for outdoor applications.



2. Applications

This PVC contact glue can be used for any type of PVC to PVC adhesion:

- Within the PVC window and door market, to joint PVC profiles, PVC angles, tubes, but also to glue false bends and shutter stocks.
- Adhesion of roofing gutters in PVC
- Within the plumbing industry to connect PVC pipes without pressure.
- Within the stand building industry or other building industry where impeccable gluing of PVC to PVC is required.

3. Instructions

The surfaces to be glued should be dry and free of dust and grease. It is advised to degrease the PVC surface, like the ANAF degreaser 2000.

Afterwards apply the glue to one of the two surfaces and then bring them together. Press them together immediately until they stay stuck. After at least 30 seconds, the initial adhesion is done. The glue hardens fast to give a high strength bond. Initial adhesion is fast, but it can take up to 4 weeks to complete full curing depending on the temperature and the surface composition/size. It is advised to apply the glue to surfaces in between 10°C and 25°C.

4. Technical characteristics

Colour:	White/transparent
Odour:	Typical
Packaging:	Aluminium tubes 150ml (cardboard 24 X 150ml)
	Metal bottle 1000ml (cardboard 6 X 1000ml)
	Other packaging on request
Viscosity:	+-2.000 mPas at 20°C.
Composition:	Composition of solvents
Usage:	Only professional

5. Storage

The glue needs to be stored away from humidity and in between a temperature of 15°C to 25°C, in a well ventilated place. The shelf life of the product is 2 year if storage rules are being respected.